

Material Safety Data Sheet

WHMIS	Protective Clothing	TDG Road / Rail
		

Section 1. Product Identification and Uses

Product Name	76243 Welders Powder Anti-Spatter	CI#	Not available.
Synonyms	Not available.	DSL	Not available.
Chemical Name	Not applicable.	CAS #	Not applicable.
Chemical Formula	Chemical mixture.	Code	1515-23-002
Chemical Family	Ketone/Polymer Additive/Silicate	Molecular Weight	Not applicable.
Supplier	Osborn International 5401 Hamilton Avenue, Cleveland, Ohio, U.S.A. 44114 PHONE: (216) 361-1900	Manufacturer	Manufactured for: Osborn International
Material Uses	Anti-Spatter.		



Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀
1) Methyl ethyl ketone	78-93-3	40-70	ORAL (LD50): Acute: 2737 mg/kg [Rat]. 3400 mg/kg [Rat]. 3600 mg/kg [Rat]. DERMAL (LD50): Acute: 13000 mg/kg [Rabbit].
2) Zinc Compound	Not available	1-5	Not available.
3) Propane	74-98-6	5-10	Not available.
4) Iso-Butane	75-28-5	10-30	Not available.

Section 3. Physical Data

Physical State and Appearance	Liquid (Aerosol Concentrate).	Odor	Characteristic.
pH (1% Soln/Water)	Not available.	Taste	Not available.
Odor Threshold	The highest known value is 0.25 ppm (Methyl ethyl ketone)	Color	Clear
Volatility	Not available.		
Evaporation Rate	5.7 (Methyl ethyl ketone) compared to Butyl acetate.		
Melting Point	Not available.		
Boiling Point	The lowest known value is 79.6 (175.3°F) (Methyl ethyl ketone).		
Density	0.812 @ 20°C (Water = 1)		
Vapor Density	The highest known value is 2.5 (Air = 1) (Methyl ethyl ketone).		
Vapor Pressure	The highest known value is 10.3 kPa (@ 20°C) (Methyl ethyl ketone).		
LogK_{ow}	Not available.		
Ionicity (Surface Active Agent)	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Conditions of Instability	Not available.		
Dispersion Properties	See solubility in water.		
Solubility	Soluble in cold water.		

Continued on Next Page



WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-2B		CONSUMER COMMODITY. ORM-D

Section 4. Fire and Explosion Data

The Product is:	Extremely Flammable Aerosol
Auto-ignition Temperature	The lowest known value is 404°C (759.2°F) (Methyl ethyl ketone).
Products of Combustion	These products are carbon oxides (CO, CO ₂), Zinc oxide fumes & other irritating gases.
Flash Points	The lowest known value is CLOSED CUP: -4.4°C (24.1°F). (Methyl ethyl ketone)
Flammable Limits	The greatest known range is LOWER: 1.8% UPPER: 11.5% (Methyl ethyl ketone)
Extinguishing Media	SMALL FIRE: Use DRY chemicals, carbon dioxide or foam. LARGE FIRE: Use foam or water fog. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Avoid spreading burning liquid with water used to cool containers. Self-contained respiratory protection should be provided for firefighters.
Flammability	The flammability of an aerosol by WHMIS definition is determined by its flame-extension or its flashback. The flame-extension of this product is greater than 45 cm. FIRE CODE: Level 3 Aerosol (as per NFPA 30B). Do not use in the presence of open flame or spark. Do not place in hot water or near radiators, stoves or other sources of heat.
Risks of Explosion	Risk of explosion of the product in presence of mechanical impact: Do not subject aerosol cans to impact. Risk of explosion of the product in the presence of static discharge: Aerosol spray may be sensitive to static discharge due to flammable concentrate and flammable propellant. Vapours of this product may form a flammable/explosive mixture with air in enclosed areas when vapours present are between the lower (1.8%) and upper (11.5%) flammable limits and come into contact with open flames, sparks or static discharge. Do NOT expose aerosol containers to open flames, heat or ignition sources. Container may explode if heated.

Section 5. Reactivity

Stability	The product is stable.
Hazardous Decomposition Products	These products are carbon oxides (CO, CO ₂), Zinc oxide fumes & other irritating gases.
Degradability	Not available.
Products of Degradation	Not available. Not available.
Corrosivity	No specific information is available in our data base regarding the corrosivity of this product in presence of various materials.
Reactivity	Avoid contact with strong oxidizing agents, strong acids and strong alkalis. Keep away from heat, sparks, open flame and all possible ignition sources.
Instability Temperature	Not available.
Conditions of Instability	Not available.

WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-2B		CONSUMER COMMODITY. ORM-D

Section 6. Toxicological Properties



Routes of Entry	Eye contact. Inhalation. Ingestion.
TLV	<p>Methyl ethyl ketone TWA: 200 CEIL: 300 TWA: 590 CEIL: 885</p> <p>Propane Simple asphyxiant.</p> <p>Consult local authorities for acceptable exposure limits.</p>
Toxicity to Animals	<p>Acute oral toxicity (LD50): 2737 mg/kg [Rat]. (Methyl ethyl ketone). Acute dermal toxicity (LD50): 13000 mg/kg [Rabbit]. (Methyl ethyl ketone). Acute toxicity of the gas (LC50): 142500 ppm 4 hour(s) [Rat]. (Iso-Butane).</p>
Chronic Effects on Humans	Prolonged or repeated skin contact may lead to dermatitis.
Acute Effects on Humans	<p>EYE CONTACT: May cause irritation, redness and tearing.</p> <p>SKIN CONTACT: May cause irritation, defatting, drying and cracking of skin.</p> <p>INHALATION: Vapours may be irritating to nose, throat and respiratory tract. Excessive inhalation of vapours may cause Central Nervous System effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.</p> <p>INGESTION: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal.</p> <p>Can be fatal if inhaled or ingested. This product may irritate eyes and skin upon contact.</p>
Synergetic Products (Toxicologically)	Not available.
Irritation/Corrosivity	See acute effects on humans.
Sensitization	Not available.
Carcinogenic Effects	Not available.
Toxic Effects on Reproduction	DEVELOPMENTAL TOXICITY: Not available.
Teratogenic Effects	TERATOGENIC EFFECTS: Not available.
Mutagenic Effects	Not available.

Section 7. Preventive Measures

Small Spill and Leak	Ventilate area and eliminate all sources of ignition. Keep away from heat. Absorb with an inert DRY material and place in an appropriate waste disposal container.
Personal Protective Equipment	Recommend safety glasses and chemical resistant gloves.
Large Spill and Leak	Not applicable for aerosol containers.
Protective Clothing	Not applicable for aerosol containers.
Engineering Controls	Use under well-ventilated conditions.
Precautions	Contents under pressure. Container may explode if heated. Direct inhalation of spray may be harmful. Keep out of reach of children.



Continued on Next Page

WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-2B		CONSUMER COMMODITY. ORM-D

Storage	Store in a cool, dry place. Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 50°C or in direct sunlight.
Handling	Do not use in the presence of open flame, sparks or ignition sources. Keep away from heat. Avoid breathing vapours or spray mists. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. After handling, always wash hands thoroughly with soap and water.
Waste Disposal	Recycle to process, if possible. Consult your local or regional authorities. Do not dispose in sewers. When container is empty, press button to release all pressure, then dispose of in garbage can.
Special Shipping Information	Not available.

Section 8. First Aid

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.
Skin Contact	Wash thoroughly with soap and water. If irritation persists, get medical attention. Remove contaminated clothing and wash before reuse.
Hazardous Skin Contact	No additional information.
Slight Inhalation	Remove affected person to fresh air. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Get medical attention.
Hazardous Inhalation	No additional information.
Slight Ingestion	If swallowed, call physician or poison control centre immediately. DO NOT induce vomiting. Rinse mouth with water. Aspiration of material into lungs due to vomiting may cause chemical pneumonitis which can be fatal.
Hazardous Ingestion	No additional information.

Section 9. MSDS Preparation

References	Not available.
No additional remark.	
Validated by Regulatory Affairs Dept. on 4/1/2002.	Verified by Regulatory Affairs Dept..
	Printed 4/2/2002.



Emergency Phone: (905) 677-1948


Responsible
Name/
Telephone No.

Classification

TDG Road / Rail	CONSUMER COMMODITY. ORM-D	
	Not applicable.	

Continued on Next Page

WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-2B		CONSUMER COMMODITY. ORM-D

<p>WHMIS</p> <p>WHMIS CLASS A: Compressed gas. WHMIS CLASS B-5: Flammable aerosol. WHMIS CLASS D-2B: Material causing other toxic effects (TOXIC).</p>	
---	---

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.