

OSBORN INTERNATIONAL  
5401 HAMILTON AVE.  
CLEVELAND; 44114  
USA

**PRODUCT: 1515-14-102 76246 COLD GALVANIZING COMPOUND****Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

MANUFACTURER ..... MANUFACTURED FOR:  
OSBORN INTERNATIONAL  
5401 HAMILTON AVE.  
CLEVELAND  
USA  
44114  
216-361-1900

PRODUCT NAME..... 1515-14-102 76246 COLD GALVANIZING COMPOUND  
CHEMICAL FAMILY..... ACRYLIC BASED COATING.  
MOLECULAR WEIGHT..... NOT APPLICABLE.  
CHEMICAL FORMULA..... MIXTURE.  
TRADE NAMES & SYNONYMS..... 1515-14-102 76246 COLD GALVANIZING COMPOUND  
PRODUCT USES..... COATING.  
FORMULA/LAB BOOK #..... 99-5006A/B.

**Section 02: COMPOSITION/INFORMATION INGREDIENTS**

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
ZINC ELEMENTAL	30-60	N/A	7440-66-6	NOT AVAILABLE	NOT AVAILABLE
TOLUENE	10-30	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
NAPHTHA	1-5	400ppm	8030-30-6	NOT AVAILABLE	NOT AVAILABLE
ISOBUTANE	7-13	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	5-10	1000 ppm	74-98-6	NOT APPLICABLE	NOT AVAILABLE

**Section 03: HAZARDS IDENTIFICATION**

ROUTE OF ENTRY:  
INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.  
INHALATION..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.

EYE CONTACT..... MAY CAUSE IRRITATION.  
SKIN ABSORPTION..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.  
SKIN CONTACT..... MAY CAUSE IRRITATION.  
EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.  
EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS  
EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

**Section 04: FIRST AID MEASURES**

EMERGENCY FIRST AID PROCEDURE ..... IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

**Section 05: FIRE FIGHTING MEASURES**

AUTO IGNITION TEMPERATURE (°C)..... 480.  
SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.  
EXTREMELY FLAMMABLE.

FLAMMABILITY.....  
IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.  
UPPER FLAMMABLE LIMIT..... 9.5.  
(% BY VOLUME)  
LOWER FLAMMABLE LIMIT..... 1.  
(% BY VOLUME)

EXPLOSION DATA  
SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.  
SENSITIVITY TO IMPACT..... NOT APPLICABLE.

HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.

AEROSOL FLAME PROJECTION  
CLASSIFIED AS:..... >45cm BUT <100cm.  
FLASHBACK..... YES.

**PRODUCT: 1515-14-102 76246 COLD GALVANIZING COMPOUND****Section 05: FIRE FIGHTING MEASURES**

FLASH POINT(°C),TAG CLOSED-CUP ..... THE LOWEST VALUE KNOWN IS TOLUENE @ 4C.  
(CONCENTRATE)

**Section 06: ACCIDENTAL RELEASE MEASURES**

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND  
NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

**Section 07: HANDLING AND STORAGE**

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.  
ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).  
HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.  
SYNERGISTIC MATERIALS..... NONE KNOWN.

**Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION**

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.  
RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR  
(NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.  
EYE/TYPE..... SAFETY GLASSES.  
FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.  
OTHER/TYPE..... NOT REQUIRED.

**Section 09: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE..... AEROSOL.  
APPEARANCE..... ALUMINIUM.  
ODOR..... AROMATIC ODOR.  
ODOR THRESHOLD..... NOT AVAILABLE.  
VAPOUR PRESSURE(PSIG)-AEROSOL..... 40-50.  
@ 20 C  
BOILING POINT (°C)(CONC)..... 93-156.  
EVAPORATION RATE..... GREATER THAN 1.  
n-BUTYL ACETATE = 1  
VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.  
(BY WEIGHT)  
SOLUBILITY IN WATER g/L (20°C)..... NEGLIGIBLE.  
pH..... NOT APPLICABLE.  
SPECIFIC GRAVITY (LIQUID)..... 2.23-2.27.  
COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.  
FREEZING POINT: (°C)..... NOT AVAILABLE.  
AEROSOL PERCENT VOLATILE..... 37-38.  
(BY WEIGHT).  
SPECIFIC GRAVITY (AEROSOL)..... 1.49-1.53.

**Section 10: STABILITY AND REACTIVITY**

HAZARDOUS PRODUCTS OF  
DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS  
INCOMPLETE.  
CHEMICAL STABILITY:  
YES..... UNDER NORMAL CONDITIONS.  
NO, WHICH CONDITIONS?..... NOT APPLICABLE.  
COMPATIBILITY WITH OTHER SUBSTANCES:  
NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.  
REACTIVITY CONDITIONS?..... NOT APPLICABLE.  
HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

**Section 11: TOXICOLOGICAL INFORMATION**

REPRODUCTIVE EFFECTS..... TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE  
(LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE  
ADVERSE FETAL DEVELOPMENTAL EFFECTS.  
IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.  
SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.  
CARCINOGENICITY OF MATERIAL..... THE INGREDIENTS OF THIS PRODUCT ARE NOT LISTED AS CARCINOGENS BY NTP,  
(NATIONAL TOXICOLOGY PROGRAM), NOT REGULATED AS CARCINOGENS BY OSHA,  
(OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION), AND HAVE NOT BEEN EVALUATED  
BY IARC,(INTERNATIONAL AGENCY FOR RESEARCH ON CANCER), NOR BY ACGIH  
(AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS).  
TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE  
ANTICIPATED.  
MUTAGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE  
ANTICIPATED.

**PRODUCT: 1515-14-102 76246 COLD GALVANIZING COMPOUND****Section 12: ECOLOGICAL CONSIDERATIONS**

ENVIRONMENTAL..... NOT AVAILABLE.

**Section 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

**Section 14: TRANSPORTATION INFORMATION**D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.  
T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).**Section 15: REGULATORY INFORMATION**

## CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,B5,D2A,D2B.  
CNFC SECTION 3.3.5..... LEVEL 1.  
CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

## U.S. REGULATIONS:

HMIS RATING FLAMMABILITY..... 2 MODERATE HAZARD.  
HMIS RATING HEALTH..... 4 SEVERE HAZARD.  
HMIS RATING REACTIVITY..... 1 SLIGHT HAZARD.  
HMIS RATING PERSONAL PROTECTION..... B.  
NFPA CODE 30B..... LEVEL 1.  
SARA 313 INFORMATION: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:  
CAS #: CHEMICAL NAME:  
\*108-88-3 TOLUENE  
. \* 7440-66-6 ZINC ELEMENTALCALIFORNIA PROPOSITION 65:..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:  
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.  
V.O.C.(M.I.R.)..... COMPLIES WITH PRIMER COATING CATERGORY OF <1.2 g OZONE / g PRODUCT.  
VOC (w/w%)..... 37-38.**Section 16: OTHER INFORMATION**

NOTICE FROM OSBORN INTERNATIONAL ..... THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY OSBORN INTERNATIONAL FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. OSBORN INTERNATIONAL ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... TECHNICAL SERVICES  
PREPARATION DATE ..... Jul02/08