

# osborn SAFETY DATA SHEET

Date Issued- 11/14/2023

SDS no. BA729/2

### **1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT DESCRIPTION	339E
CHEMICAL NAME	Blended abrasive solid
GENERAL USE	Polish for metal finishing
MANUFACTURER ADDRESS	Osborn
	3440 Symmes Rd. Hamilton
	OH 45015 USA
CONTACT NUMBER	1-513-860-3400
EMERGENCY CONTACT	PLANT OPERATIONS
EMERGENCY PHONE	1-513-678-3672
24 HOUR EMERGENCY	
TELEPHONE NUMBER	CHEMTREC (24 HOURS) 800-424-9300
2. HAZARD IDENTIFICATION	

#### **EMERGENCY OVERVIEW**

IMMEDIATE CONCERNS		May cause eye or skin irritati		rotective
	equipment	should be worn. Wash skin a	after use.	
POTENTIAL HEALTH EFFECTS				
Eye:	May cause	eye irritation		
Skin	May cause	mild skin irritation		
Ingestion	Large oral	doses may cause irritation		
Inhalation	Avoid brea	thing dust when used in a bu	Iffing process	
Chronic	None expe	cted		
GHS Label requirements				
Pictogram None				
Signal Word None				
Hazard Statement				
Precautionary Statements				
P261	Avoid brea	thing dust from buffing oper	ations	
P264	Wash thor	oughly after handling		
P280	Wear portective gloves/protective clothing/eye protection/ face protection			
P302+P352	If on Skin:	Wash with soap and water		
P305+P351	If in eyes: \	Nash cautiously with water f	or 15 minute	S.
3. COMPOSITION/INGRED	IENT INF	ORMATION		
Ingredients	CAS	PEL/ TLV	Weight %	
Aluminum Oxide	1344-28-1	10 mg/ M3	65-80%	
Fatty Acid /Glyceride		Not Hazardous	18-24%	

Petroleum Oil or Wax	Not Hazardous	2-6%

4. FIRST AID MEASURES Inhalation	If exposed to excessive levels of dust, remove to fresh air.
Innalation	
	Get medical attention if cough, irritation or other symptoms develop.
Skin Contact	Wash with soap and water.
	Get medical attention if irritation or rash develop.
Eye Contact	Immediately flush eyes with plenty of water for 15 minutes.
	If abrasive particles are not removed, obtain medical attention.
Ingestion	Swallowing less than an ounce will not cause significant harm.
	For larger amounts do not induce vomiting,
	but give two 12 ounce glasses of water and obtain medical advice.
<b>5. FIRE FIGHTING MEASU</b>	IRES
Flash Point	>350 F
Extinguishing Media	Use alcohol foam, carbon dioxide, or dry chemical
	when fighting fires involving this material.
Fire fighting Procedure	Remove ignition source and fight fire as if it were a grease fire.
-	
Special Protective Equipment	As in any fire, wear self contained breathing apparatus (pressure-demand,
	MSHA/NIOSH approved or equivalent) and full protective gear.

Products	and carbon dioxide
Hazardous Combustion	If heated to high temperature the product may emit carbon monoxide
	instruction approved of equivalency and run protective gear.

#### **6 ACCIDENTAL RELEASE MEASURES**

**Environmental Precautons** 

None known

Methods for Clean upSweep or Scoop up material for reuse or reclaim if possible,<br/>otherwise place in a disposal container for proper disposition.

7. HANDLING AND STOR	AGE
Handling	No special handling requirements are known
Storage	Keep out of sun and away from heat sources, as product may melt. Observe all safeguards for container residue until cleaned or destroyed. Do not flush to sewers or waterways unless authorized to do so by appropriate government official.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

	LINGOIN			
Exposure Limit Values	10 mg/ m	i3 as dust		
Engineering Measures	Ventilatic	on to keep dust level at ex	posure limits	
		·		
Hygiene Measures				
<b>Respiratory Protection</b>	Wear a d	ust mask		
Hand Protection	Wear gloves			
Eye Protection	Wear safety glasses with side shields or goggles			
Skin Protection	Wash wit	h soap and water before	eating or after shif	ťt
9. PHYSICAL AND CHEMIC	AL PROP	PERTIES		
Physical State	Solid	Solubility in Water	None	
Color	White	Flash Point	>350F	
Boiling Point	N/A	Vapor Density	N/A	
Melting Point	135 F	<b>Evaporation Rate</b>	N/A	

	-	• •	-
Melting Point	135 F	<b>Evaporation Rate</b>	N/A
Specific Gravity	> 1.3	Odor	Mild;
рН	N/A	VOC	None
Autoignition Temperature	N/A		

10. STADILITT AND REACTIVITT		
Stability	Product is stable	
Conditions to Avoid	Material can ignite if exposed to a continuous flame	or heat source
Incompatible Materials	None known	
Hazardous Decomposition Products	If product is involved in a fire, carbon monoxide coul	d be emitted
Hazardous Polymerization	Will Not occur	

Eyes	May cause irritation from abrasion.	
Skin Contact	May cause irritation	
Skin Absorption	Not likely	
Inhalation	Dust form buffing operation may cause irritation	
Swallowing	No adverse effect is expected	
12. ECOLOGICAL INFORMATION		

Ecological Information

No data available

Bioaccumulative Potential Bio

Bioaccumulation is unlikey

**Comments** This product is not believed to be toxic to aquatic life.

#### **13. DISPOSAL CONSIDERATIONS**

General	If discarded, the material in its original unused form is not a RCRA hazardous waste.
	Disposal should be in accordance with State and Local regulations for the
	disposal of non-hazardous waste. Be sure to check if compound (after used)
	has come in contact with a hazardous substance before disposal

Packaging Dispose in clean receptical or box.

## **14. TRANSPORTATION INFORMATION** DOT Not regulated Classification **IMDG Classification** Not regulated **ICAO Classification** Not regulated **15. REGULATORY INFORMATION UNITED STATES** Sara Title III 313 Reportable Ingredients None 302/304 Emergency Planning **Emergency Plan CERCLA (Comprehensive Response, Compensation and Liability Act) CERCLA RQ** None **EPA HAZARD CATEGORIES** SARA 311/312 - None **TSCA (Toxic Substance Control Act)** TSCA Status - All ingredients are on the TSCA list **16. OTHER INFORMATION Revision Number** BA729-5 1/1/2015 **Supersedes Date HMIS Rating** 1-1-0-0 **Manufacturer Disclaimer** Metal Dusts from the buffing of brass, zinc and especially magnesium or aluminum along with buffing cloth fibers and compound residues may cause fires or explosions when exposed to a strong ignition source. These fires typically are started in the vent pipes, collector bags or receptacles used in waste gathering from the buffing ventilation system. Make sure that the collectors are changed frequently and the waste kept in a cool, dry environment that is free from sparks or other strong ignition sources. The collection devices should be grounded to minimize static charges.Dust collection receptacles should be designed by engineers who are familiar with the potential hazard of a flammable or explosive dust. If such a fire occurs, fight the fire with a Class D fire extinguisher. Do not use water or a halogenated extinguishing media.