



SAFETY DATA SHEET

Date Issued- 1/1/2024

SDS no. BA-559

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION A-6
CHEMICAL NAME Blended abrasive solid

GENERAL USE Polish for metal finishing
MANUFACTURER ADDRESS Osborn
 3440 Symmes Rd. Hamilton
 OH 45015 USA

CONTACT NUMBER 1-513-860-3400
EMERGENCY CONTACT PLANT OPERATIONS
EMERGENCY PHONE 1-513-678-3672
24 HOUR EMERGENCY TELEPHONE NUMBER CHEMTREC (24 HOURS) 800-424-9300

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS Danger! Contains silica. Dust from buffing operation may cause damage to the lungs. May also irritate the eyes and the skin. Protective equipment should be worn. Wash skin after use.

POTENTIAL HEALTH EFFECTS

Eye: May cause eye irritation
 Skin: May cause mild skin irritation
 Ingestion: Large oral doses may cause irritation
 Inhalation: Product as supplied is not hazardous. May cause serious health damage due to breathing dust from buffing operation with this material
 Chronic: Silicosis, Cancer

GHS Label requirements

Pictogram --



Signal Word--- Danger

Hazard Statement

H372 Causes damage to lungs through repeated breathing of dusts resulting from buffing operations with this material

Precautionary Statements

P260 Do not breath dusts from buffing operation with this material
 P285 In case of inadequate ventilation, wear respiratory protection
 P280 Wear portective gloves/protective clothing/eye protection/ face protection

P302+P352

If on Skin: Wash with soap and water

P305+P351

If in eyes: Wash cautiously with water for 15 minutes.

3. COMPOSITION/INGREDIENT INFORMATION

| Ingredients | CAS | PEL/ TLV | Weight % |
|-----------------------|------------|---------------|----------|
| Silica | 14808-60-7 | 0.1 mg/M3 | 2-10% |
| Aluminum Oxide | 1344-28-1 | 10 mg/M3 | 50-80% |
| Fatty Acid /Glyceride | | Not Hazardous | 18-35% |
| Petroleum Oil or Wax | | Not Hazardous | 2-8% |
| | | | |

4. FIRST AID MEASURES

| | |
|---------------------|---|
| Inhalation | If exposed to excessive levels of dust, remove to fresh air. Get medical attention if cough, irritation or other symptoms develop. |
| Skin Contact | Wash with soap and water. Get medical attention if irritation or rash develop. |
| Eye Contact | Immediately flush eyes with plenty of water for 15 minutes. If abrasive particles are not removed, obtain medical attention. |
| Ingestion | Swallowing less than an ounce will not cause significant harm. For larger amounts do not induce vomiting, but give two 12 ounce glasses of water and obtain medical advice. |

5. FIRE FIGHTING MEASURES

| | |
|--------------------------------------|--|
| Flash Point | >350 F |
| Extinguishing Media | Use alcohol foam, carbon dioxide, or dry chemical when fighting fires involving this material. |
| Fire fighting Procedure | Remove ignition source and fight fire as if it were a grease fire. |
| Special Protective Equipment | As in any fire, wear self contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear. |
| Hazardous Combustion Products | If heated to high temperature the product may emit carbon monoxide and carbon dioxide |

6 ACCIDENTAL RELEASE MEASURES

Environmental Precautions None known

Methods for Clean up Sweep or Scoop up material for reuse or reclaim if possible, otherwise place in a disposal container for proper disposition.

7. HANDLING AND STORAGE

Handling No special handling requirements are known

Storage Keep out of sun and away from heat sources, as product may melt.
Observe all safeguards for container residue until cleaned or destroyed.
Do not flush to sewers or waterways unless authorized to do so by appropriate government official.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|-------------------------------|--|
| Exposure Limit Values | 0.1 mg/ M3 as dust resulting from the buffing operation with this material |
| Engineering Measures | Ventilation to keep dust level at exposure limits |
| Hygiene Measures | |
| Respiratory Protection | Wear respiratory protection such as a dust mask |
| Hand Protection | Wear gloves |
| Eye Protection | Wear safety glasses with side shields or goggles |
| Skin Protection | Wash with soap and water before eating or after shift |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|---------------------------------|-----------|----------------------------|-------|
| Physical State | Solid | Solubility in Water | None |
| Color | Black | Flash Point | >350F |
| Boiling Point | N/A | Vapor Density | N/A |
| Melting Point | 125 deg.F | Evaporation Rate | N/A |
| Specific Gravity | >1.3 | Odor | Mild; |
| pH | N/A | VOC | None |
| Autoignition Temperature | N/A | Freezing Point | N/A |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Stability | Product is stable |
| Conditions to Avoid | Material can ignite if exposed to a continuous flame or heat source |
| Incompatible Materials | None known |
| Hazardous Decomposition Products | If product is involved in a fire, carbon monoxide could be emitted |
| Hazardous Polymerization | Will Not occur |

11. TOXICOLOGICAL INFORMATION

| | |
|------------------------|---|
| Eyes | May cause irritation from abrasion. |
| Skin Contact | May cause irritation |
| Skin Absorption | Not likely |
| Inhalation | Dust from buffing operation includes silica which may cause silicosis, a lung disease. Silica is also found to cause lung cancer in humans. |
| Swallowing | No adverse effect is expected |

12. ECOLOGICAL INFORMATION

| | |
|----------------------------------|---|
| Ecological Information | No data available |
| Bioaccumulative Potential | Bioaccumulation is unlikely |
| Comments | This product is not believed to be toxic to aquatic life. |

13. DISPOSAL CONSIDERATIONS

| | |
|----------------|---|
| General | If discarded, the material in its original unused form is not a RCRA hazardous waste. Disposal should be in accordance with State and Local regulations for the |
|----------------|---|

disposal of non-hazardous waste. Be sure to check if compound (after used) has come in contact with a hazardous substance before disposal

Packaging Dispose in clean receptical or box.

14. TRANSPORTATION INFORMATION

| | |
|---------------------|---------------|
| DOT Classification | Not regulated |
| IMDG Classification | Not regulated |
| ICAO Classification | Not regulated |

15. REGULATORY INFORMATION

UNITED STATES

Sara Title III

313 Reportable Ingredients - 1344-28-1 aluminum oxide
302/304 Emergency Planning None
Emergency Plan Report as required by the state and local agencies for both product and waste

California Prop 65-

WARNING: This product contains a chemical known to the State of California to cause cancer and/or reproductive harm.

| <u>Ingredient</u> | <u>Cancer</u> | <u>Reproductive</u> |
|-------------------|---------------|---------------------|
| Silica | Yes | No |
| Titanium Dioxide | Yes | No |

CERCLA (Comprehensive Response, Compensation and Liability Act)

CERCLA RQ None

EPA HAZARD CATEGORIES

SARA 311/312 - product contains silica

TSCA (Toxic Substance Control Act)

TSCA Status - All ingredients are on the TSCA list

16. OTHER INFORMATION

Revision Number BA-559-6
Supersedes Date 1/1/2018

HMIS Rating 1-1-0-0

Manufacturer Disclaimer

Metal Dusts from the buffing of brass, zinc and especially magnesium or aluminum along with buffing cloth fibers and compound residues may cause fires or explosions when exposed to a strong ignition source. These fires typically are started in the vent pipes, collector bags or receptacles used in waste gathering from the buffing ventilation system. Make sure that the collectors are changed frequently and the waste kept in a cool, dry environment that is free from sparks or other strong ignition sources. The collection devices should be grounded to minimize static charges. Dust collection receptacles should be designed by engineers who are familiar with the potential hazard of a flammable or explosive dust. If such a fire occurs, fight the fire

with a Class D fire extinguisher. Do not use water or a halogenated extinguishing media.