

Date Issued- 6/1/2015

SDS no. BS-758

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION R3200A

CHEMICAL NAME Blended abrasive solid

GENERAL USE Polish for metal finishing

MANUFACTURER ADDRESS Osborn

3440 Symmes Rd. Hamilton

OH 45015 USA

CONTACT NUMBER 1-513-860-3400
EMERGENCY CONTACT PLANT OPERATIONS
EMERGENCY PHONE 1-513-678-3672

24 HOUR EMERGENCY

TELEPHONE NUMBER CHEMTREC (24 HOURS) 800-424-9300

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS	CAUTION! May cause eye or skin irritation. Proper protective
	equipment should be worn. Wash skin after use.

POTENTIAL HEALTH EFFECTS

Eye: May cause eye irritation
Skin May cause mild skin irritation

Ingestion Large oral doses may cause irritation

Inhalation Avoid breathing dust when used in a buffing process

Chronic None expected

GHS Label requirements

Pictogram -- None Signal Word--- None Hazard Statement

Precautionary Statements

P261 Avoid breathing dust from buffing operations

P264 Wash thoroughly after handling

P280 Wear portective gloves/protective clothing/eye protection/ face protection

P302+P352 If on Skin: Wash with soap and water

P305+P351 If in eyes: Wash cautiously with water for 15 minutes.

3. COMPOSITION/INGREDIENT INFORMATION

Ingredients	CAS	TLV: PEL	Weight %
Iron Oxide	1309-37-1		70-90%

Nonyl Phenol Ethoxylate	127087-87-1		>1%
Fatty Acid /Glyceride		Not Hazardous	10-15%
Petroleum Oil/Wax		Not hazardous	>3%

4. FIRST AID MEAS	SURES
Inhalation	If exposed to excessive levels of dust, remove to fresh air.
	Get medical attention if cough, irritation or other symptoms develop.
Skin Contact	Wash with soap and water.
	Get medical attention if irritation or rash develop.
Eye Contact	Immediately flush eyes with plenty of water for 15 minutes.
	If abrasive particles are not removed, obtain medical attention.
Ingestion	Swallowing less than an ounce will not cause significant harm.
	For larger amounts do not induce vomiting,

5. FIRE FIGHTING MEASURES

Flash Point	>350 F
Extinguishing Media	Use alcohol foam, carbon dioxide, or dry chemical
	when fighting fires involving this material.
Fire fighting Procedure	Remove ignition source and fight fire as if it were a grease fire.
Special Protective Equipment	As in any fire, wear self contained breathing apparatus (pressure-demand,
	MSHA/NIOSH approved or equivalent) and full protective gear.
Hazardous Combustion	If heated to high temperature the product may emit carbon monoxide
Products	and carbon dioxide

but give two 12 ounce glasses of water and obtain medical advice.

6 ACCIDENTAL RELEASE MEASURES

Environmental Precautons None known

Methods for Clean up Sweep or Scoop up material for reuse or reclaim if possible,

otherwise place in a disposal container for proper disposition.

7. HANDLING AND STORAGE

Handling No special handling requirements are known

Storage Keep out of sun and away from heat sources, as product may melt.

Observe all safeguards for container residue until cleaned or destroyed.

Do not flush to sewers or waterways unless authorized to do so

by appropriate government official.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limit Values	10 mg/ m3 as dust
Engineering Measures	Ventilation to keep dust level at exposure limits

Hygiene Measures

Respiratory Protection Wear a dust mask
Hand Protection Wear gloves

Eye Protection Wear safety glasses with side shields or goggles **Skin Protection** Wash with soap and water before eating or after shift

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Solid	Solubility in Water	None
Color	Red	Flash Point	>350F
Boiling Point	N/A	Vapor Density	N/A
Melting Point	135 F	Evaporation Rate	N/A
Specific Gravity	> 1.3	Odor	Mild;
рН	N/A	voc	None
Autoignition Temperature	N/A		

10. STABILITY AND REACTIVITY

Stability	Product is stable	
Conditions to Avoid	Material can ignite if exposed to a continuous flame	or heat source
Incompatible Materials	None known	
Hazardous Decomposition Products	If product is involved in a fire, carbon monoxide cou	d be emitted
Hazardous Polymerization	Will Not occur	

11. TOXICOLOGICAL INFORMATION

Eyes		May cause irritation from abrasion.
Skin (Contact	May cause irritation
Skin /	Absorption	Not likely
Inhal	ation	Dust form buffing operation may cause irritation
Swall	lowing	No adverse effect is expected

12. ECOLOGICAL INFORMATION

Ecological Information No data available

Bioaccumulative Potential Bioaccumulation is unlikey

Comments

This product is not believed to be toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

General If discarded, the material in its original unused form is not a RCRA hazardous waste.

Disposal should be in accordance with State and Local regulations for the disposal of non-hazardous waste. Be sure to check if compound (after used)

has come in contact with a hazardous substance before disposal

Packaging Dispose in clean receptical or box.

14. TRANSPORTATION INFORMATION

DOT Not regulated

Classification

IMDG Classification

Not regulated

ICAO Classification

Not regulated

15. REGULATORY INFORMATION

UNITED STATES

Sara Title III

313 Reportable Ingredients - None 302/304 Emergency Planning

Emergency Plan

CERCLA (Comprehensive Response, Compensation and Liability Act)

CERCLA RQ - None

EPA HAZARD CATEGORIES

SARA 311/312 - None

TSCA (Toxic Substance Control Act)

TSCA Status - All ingredients are on the TSCA list

16. OTHER INFORMATION

Revision Number BS758-5

Supersedes Date 1/1/2014

HMIS Rating 1-1-0-0

Manufacturer Disclaimer Metal Dusts from the buffing of brass, zinc and especially magnesium or aluminum

along with buffing cloth fibers and compound residues may cause fires or explosions when exposed to a strong ignition source. These fires typically are started in the vent pipes, collector bags or receptacles used in waste gathering from the buffing ventilation system. Make sure that the collectors are changed frequently and the

waste kept in a cool, dry environment that is free from sparks or other strong ignition

sources. The collection devices should be grounded to minimize static charges. Dust collection receptacles should be designed by engineers who are familiar with the potential hazard of a flammable or explosive dust. If such a fire occurs, fight the fire with a Class D fire extinguisher. Do not use water or a halogenated extinguishing media.